

NATIONAL

CUSTOM HOLLOW METAL DOORS & FRAMES

PH: 501-372-3441 PH: 1-800-334-3070
 P.O. Box 428 - Little Rock, AR 72203-0428
 NCHMetal.com DefendDoor.com
 Fax: 501-375-3070

Purchase Order No.

Quote No.



Job Name:

Date Submitted:		Door Order/ Quote Form				DOOR STYLE														
Contact Name:			F	HG	FG	VL	NL	LV		DD										
Company Name:																				
Ship to Address:																				
Phone #																				
FAX #																				
Lead Time:		Circle: 1 2 3 4 5 6 7 8 9 10 (Days) 3 or 4 Weeks																		

Door Style / Material Description					Door Size				Door Construction					Hardware Preps / Other						Unit	Cost						
Item Number	Quantity	Door Style	Material: A60 Galv	Material: 304 / 316 S.S.	S.S. Finish: 2B or #4	Opening Width (inches)		Opening Height (inches)		Net Width	Net Height	Gauge	Handing	Core	Thickness	Undercut	Edge Construction	Fire Rating	Locations	Hinges	Lock/Strike	Closer Reinf.	Lead Option	Astragal	Unit	Cost	
						FT	IN	FT	IN																		
1																											
Special Instructions:																											
2																											
Special Instructions																											
3																											
Special Instructions																											
4																											
Special Instructions																											
5																											
Special Instructions																											
6																											
Special Instructions																											

Sub Total = \$0.00 Estimated Freight =

Hinge Preps (*Template Required)		Lock/Strike Preps (*Template Required)		Astragal		Hardware Locations		Special Locations		GK / Louver C.O. Loc.		Core Type	
A. 4 1/2" SW	I. Elec. Hinge*	A1. 161	A9. Panic Reinf.	A. Flat Astragal	A = Amweld	Z = Deansteel	L1.	A.	A. Polycore				
B. 4 1/2" HW	J. Invisible*	A2. Push/Pull	IA1. ASA	B. Z Astragal	C = Ceco	M = Mesker	L2.	B.	B. Steel Stiff.				
C. 5" SW	K. 4" SW	A3. 161 w/161 DL	IA2. ASA x FB	Edge Construction	F = Fenestra	K = Kewanee	H1.	C.	C. Honeycomb				
D. 5" HW	L. 4" HW	A4. 161 w/ (3) 161 DL	IA2. ASA x DL	A. Exposed Seam	R = Republic	U = Curries	H2.	Lead Option		Fire Rating			
E. 3 1/2" SW	M. Anchor*	A5. Mortise*	IA3. T/B FB Only	B. Seamless Edges	S= Steelcraft	P = Pioneer	H3.	A. 1/32"	A. 3HR				
F. Pivots*	O. Other*	A6. SVR*	IA4. ASA x Surf. Bolt	C. Epx Seam w/Flush Top Cap	DKS = DKS	D = Premier	H4.	B. 1/16"	B. 90min				
G. Continuous Hinge on Edge*		A7. CVR*	IA5. Surf. Bolt	D. 3 Sided Seamless (Top)	E = 5-10-Equal	X = Special	H5.	C. 1/8"	C. 45min				
H. Continuous Hinge on Face*		A8. Panic Prep*	IA6. Surf. Mnt Strike	E. 4 Sided Seamless	OR= Old Republic			D. 1/4"	D. 20min				

I APPROVE THIS ORDER TO BE MADE TO THE SPECIFICATIONS LISTED ON THIS FORM:
 Signature: _____

NCHM Quality Control will check each door and component part to assure we have filled your order properly. However, final responsibility that the material purchased is correct will be with the purchaser. We will correct any error on our part immediately. If the material is sent to and/or installed at the job site wrong, the purchaser accepts all responsibility.